

# APEX OVERFLOW SLOTS

**NEW  
OVERFLOW  
SLOT PATTERN**

## QUAD 115mm HIFRONT GUTTER

Apex has redesigned and increased the overflow slot pattern of our Quad HiFront 115mm Gutter to assist in compliance with the new Overflow regulations of the NCC 2016.

For roof sheet lengths over 15m, our SC5 combined spacer/spring clip or other systems as per our current Overflow Solutions Manual must still be used.

## APEX GUTTER AND FASCIA

**Effective from Monday 1st May 2017,  
ALL orders received will be supplied in the  
NEW standard big slot profile.**

NB. For match ups of existing installations the old profile can be custom made on a 3 day lead time. Should this be required the order must clearly be specified "small slot" at time of order placement.

Please note when installing the minimum distance from the top of the fascia to bottom of the new slots is 25mm.

The new larger overflow slot area (2070mm<sup>2</sup>/m) will satisfy the NCC 2016 requirements for a maximum roof sheet length (ridge to gutter) up to 15.000m in SEQ without a spacer.

Should you require a copy of the Form 15 Compliance Certificate or have any other queries please contact your account manager or our sales office team.

**APEX**  
apexsteel.com.au

4 Cojo Place, Dandenong South VIC 3175  
Telephone: (03) 9768 4777

For further information please refer to our website or contact you're closest Apex Sales Office. Colorbond and Zinalume are registered trademarks of BlueScope Steel Limited. 03/17